

HYGIstrat

Locker with integrated boot dryer



Remarkable combination of a locker and a boot dryer

Locker:

- 2 widths available: 300 mm (clean industry) and 400 mm (dirty industry)
- HPL laminate (comply with the EN438 norm) – panel's thickness of 8 mm
- Impact, scratch, abrasion, steam proof (M2 class certified)
- Rot-proof: water or foam washable
- Antibacterial (food contact certified)
- Equipements: sloping roof, upper shelf, rod hanger, "clean/dirty" partition (w. 400 mm), locking system and name label
- 10 colours available
- 2-year warranty

Boot dryer:

- Adapted to boots and shoes
- **3 to 16 pairs in single or double side**
- 100% stainless steel 304L construction
- Water or foam washable thanks to the specific **covering made with chicanes**
- Chassis equipped with adjustable stainless steel/plastic feet
- **2-year warranty on all spare parts**
- **Made in France** 🇫🇷

Efficient and economical drying

- Warm drying in **less than 1 hour** thanks to the powerful cooling system coupled with a heating element
- Stainless steel boot tube holder equipped with a valve activated by the weight of the boot or the shoe
- **Preserves** the technical properties of the boots or shoes and **extends** also the lifetime
- Cycle programming via a programmable plug for automatic start and stop
- Barely more the 0,5 kW/hour required for a complete cycle

Unrivalled level of hygiene

- **Disinfection** guaranteed by a germicidal lamp with ozone production that totally eliminates bacteria responsible for bad smells and skin diseases (Cycle duration: 1 h 30)
- **Deodorization acquires only** through the ozone abilities, without any additional chemical products
- Sanitizing abilities tested and approved by a **Veterinary Analysis Laboratory**

Options

- The HPL laminate locker are also available in full height 1830/2270 mm on feet
- Code locking system
- Movable "clean/dirty" party (non-detachable)
- Integrated bench (Boot dryer)

Unit width (mm)	Number of lockers	Construction		Configuration	Dimensions W x H x D (mm)	Power supply	Consumption
		Locker	Boot dryer				
300	3 to 8	HPL Laminate EN 438	Stainless steel	Single or double side	905 to 2415 x 2110 x 505/1010	1 x 230V / 10-16 A / 50-60 Hz	550 W
400	3 to 6				1245 to 2485 x 2110 x 505/1010		

Technical specifications subject to variations